

DOWNLIGHT

**WARMDIM.
OPTION DIMBAR
KELVIN**

**ANVÄNDINGS-
OMRÅDEN**

- Butik
- Kontor
- Mässa
- Utställning

Optik: Reflektor
Material: Aluminium
Ljuskälla: LED

Egenskaper

Diameter	75mm - 150mm
Effekter	6W -88W
Vikt	0,4kg - 3,00kg
Täthetsklass	IP20
Vandalklass	X
Elsäkerhetsklass	I alt. II



SPECIFIKATION

Certifierad:	Nej, IP20, armatur uppfyller kraven i EN60598
Programmerbar version:	Nej (för andra modeller fråga om offert)
Ej programmerbara versioner:	6w upp till 88W
Ljusutbyte:	90-110lm/W
Korrelerad färgtemperatur:	3000K som standard alt. 4000K dimbar Kelvin beställningsvara
Färgåtergivningsindex:	CRI90
SDCM:	>4
Bibehållet ljusflöde enligt L80:	50,000h IESNA LM80
Temperaturintervall vid drift:	-35° till +35°C
Underhåll:	Skruvmejsel och ringnyckel
Nätspänning:	100-240 V AC/50-60 Hz
EMC:	Driver/armatur enligt EN55015,EN61000-2-3,EN61547
Optik:	Frostat alt. centerfrostat alt. klart glas
Material:	Kylning pressgjuten aluminium, aluminium, plast
Vikt:	0,4 - 3,00 kg
Färg:	Natureloxerad aluminium
Montering / fäste:	Infällda
Rekommenderad montagehöjd:	2m-15 beroende på effekt och ändamål
Förmonterad installationskabel:	Offert

Option/tilval:

Styrsystem:	0-10V styrning alt. Dali
--------------------	--------------------------



**WARMDIM.
OPTION DIMBAR
KELVIN**





180° roterbar																																
Item no.	LED Power	Lamp Power	Color Kelvin (optional)	Voltage	Beam angle (optional)	Glasses (optional)	Color of housing (optional)	Dimension (mm)	Dim types (optional)	Lamp lumen																						
D0675	6W	7.5W	2700K 3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	∅ 90*H60 ∅ 75 (hole)	Not-dim Triac 1-10V Dali	570-630lm																						
											D1095	10W	11.5W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	∅ 110*H70 ∅ 95 (hole)	Not-dim Triac 1-10V Dali	1150-1350lm											
																						D20120	20W	23W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	∅ 138*H85 ∅ 120 (hole)	Not-dim Triac 1-10V Dali	2200-2600lm
D40165	40W	45W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white silver black	∅ 180*H105 ∅ 165 (hole)	Not-dim Triac 1-10V Dali	4100-4800lm																						
											D50200	50W	55W	3000K 4000K	AC200-240V	35° 65°	clear frosted center-frosted	white silver black	∅ 230*H115 ∅ 200 (hole)	Not-dim Triac 1-10V Dali	5600-6400lm											



**WARMDIM.
OPTION DIMBAR
KELVIN**

360° roterbar																					
Item no.	LED Power	Lamp Power	Color Kelvin (optional)	Voltage	Beam angle (optional)	Glasses (optional)	Color of housing (optional)	Dimension (mm)	Dim types (optional)	Lamp lumen											
D20170	20W	23W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white black	∅ 198x131 ∅ 170 (hole)	Not-dim Triac 1-10V Dali	2200-2600lm											
											D30170	30W	34.5W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white black	∅ 198x131 ∅ 170 (hole)	Not-dim Triac 1-10V Dali	3300-3700lm



**WARMDIM.
OPTION DIMBAR
KELVIN**



STRIHL SCANDINAVIA AB
WWW.STRIHL.SE
+46 (0)300-569980



Vertikalt justerbara, 90° roterbar

Item no.	LED Power	Lamp Power	Color Kelvin (optional)	Voltage	Beam angle (optional)	Glasses (optional)	Color of housing (optional)	Dimension (mm)	Dim types (optional)	Lamp lumen
G10140	10W	11.5W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white black	∅ 151*H134 ∅ 140 (hole)	Not-dim	1150-1350lm
									Triac	
									1-10V	
G15140	15W	17.5W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white black	∅ 151*H134 ∅ 140 (hole)	Dali	1700-1900lm
									Not-dim	
									Triac	
G20175	20W	23W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white black	∅ 185x160 ∅ 175 (hole)	1-10V	2200-2600lm
									Dali	
									Not-dim	
G30175	30W	34.5W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white black	∅ 185x160 ∅ 175 (hole)	Triac	3300-3700lm
									1-10V	
									Dali	



**WARMDIM.
OPTION DIMBAR
KELVIN**



Fyrkantig ram , 180° roterbar

Item no.	LED Power	Lamp Power	Color Kelvin (optional)	Voltage	Beam angle (optional)	Glasses (optional)	Color of housing (optional)	Dimension (mm)	Dim types (optional)	Lamp lumen
C06751	1x6W	7.5W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	92x92x70 ø 75(hole)	Not-dim	570-630lm
									Triac	
									1-10V	
									Dali	
C06752	2x6W	15W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	Not-dim	1100-1260lm	
								Triac		
								1-10V		
								Dali		
C06753	3x6W	22.5W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	Not-dim	1700-1890lm	
								Triac		
								1-10V		
								Dali		
C10951	1x10W	11.5W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	Not-dim	1150-1350lm	
								Triac		
								1-10V		
								Dali		
C10952	2x10W	23W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	Not-dim	2300-2700lm	
								Triac		
								1-10V		
								Dali		
C10953	3x10W	34.5W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	Not-dim	3400-4000lm	
								Triac		
								1-10V		
								Dali		
C201201	20W	23W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	Not-dim	2200-2600lm	
								Triac		
								1-10V		
								Dali		
C201202	2x20W	45W	3000K 4000K	AC200-240V	30° 50°	clear frosted center-frosted	white silver black	Not-dim	4400-5200lm	
								Triac		
								1-10V		
								Dali		
C301451	30W	34.5W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white silver black	Not-dim	3300-3700lm	
								Triac		
								1-10V		
								Dali		
C301452	2x30W	68W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white silver black	Not-dim	6600-7200lm	
								Triac		
								1-10V		
								Dali		
C401651	40W	45W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white silver black	Not-dim	4100-4800lm	
								Triac		
								1-10V		
								Dali		
C401652	2x40W	88W	3000K 4000K	AC200-240V	25° 55°	clear frosted center-frosted	white silver black	Not-dim	8200-9600lm	
								Triac		
								1-10V		
								Dali		



**WARMDIM.
OPTION DIMBAR
KELVIN**